

Single Or Dual Nozzle CNG Fuel Dispenser 25L/Min Gas Pump CNG



Product Specification

• Temperature Range:	-25 To +55
• Display:	LCD
Humidity Range:	≤95%
Power Supply:	AC 220V/50Hz
Communication Interface:	RS485/RS232
Unit Price Range:	0.01-99.99
Accuracy:	±0.5%
Working Pressure:	20MPa
Highlight:	251/min gas pump cng, cng fuel dispenser 251, cng fuel dispenser 251/min

Fit For Tough Environment Single Or Dual Nozzle CNG Fuel Dispenser,

Product Description:

With a hose length of 4m, the CD-100 model is perfect for both small and large vehicles alike. The power supply of AC 220V/50Hz ensures that you can easily and quickly replenish your vehicle's natural gas tanks with minimal downtime. Whether you're a busy commercial fleet owner or an individual who wants to save money on fuel costs, the CD-100 model is the perfect solution for you. Choose between a single or dual nozzle option to suit your needs. The CD-100 model is built to handle high flow rates, so you can be sure that your vehicles will be fueled quickly and efficiently. The nozzle also features a durable design that can withstand frequent use, ensuring that your investment lasts for years to come.

The CD-100 model is also designed to operate in a wide range of humidity conditions, with a range of up to \leq 95%. This means that you can use it in almost any weather condition, making it a versatile and reliable solution for all of your CNG fueling needs. Overall, the CD-100 model is a top-of-the-line CNG Fueling Equipment that is perfect for anyone who wants to switch to natural gas. With its efficient design, reliable operation, and ability to handle high flow rates, it's the perfect solution for any fleet or individual looking to save money on fuel costs.

Features:

 Product Name: CNG Gas Dispenser

 Flow Rate: 15-25L/min

 Working Pressure: 20MPa

 Display: LCD

 Power Supply: AC 220V/50Hz

 Humidity Range: ≤95%

 This CNG Gas Dispenser is also known as a CNG Refueling Machine, CNG Distribution Pump, or CNG Fueling Equipment.

Technical Parameters:

Model	CD-100
Display	LCD
Humidity Range	≤95%
Flow Rate	15-25L/min
Accuracy	±0.5%
Power Supply	AC 220V/50Hz
Nozzle	Single Or Dual
Unit Price Range	0.01-99.99
Temperature Range	-25 To +55
Communication Interface	RS485/RS232

Applications:

It can be used in various application occasions and scenarios, including:

Gas Stations: The Virette CD-100 CNG Gas Dispenser can be used in gas stations to provide CNG refueling services to customers with CNG-powered vehicles. It can be used as a standalone CNG fueling equipment or can be integrated with other fuel dispensers.

Public Transportation: Public transportation organizations can use the Virette CD-100 CNG Gas Dispenser to refuel their CNG-powered buses, taxis, and other vehicles. It can help them reduce their operating costs and promote the use of clean energy.

Industrial Facilities: Industrial facilities that use CNG-powered equipment can use the Virette CD-100 CNG Gas Dispenser to refuel their equipment. It can help them save money on fuel costs and reduce their carbon footprint.

The Virette CD-100 CNG Gas Dispenser has a temperature range of -25 to +55 and a working pressure of 20MPa, making it suitable for use in different environments and weather conditions. It also has a humidity range of \leq 95%, ensuring that it operates effectively in humid environments.

The total price range for the Virette CD-100 CNG Gas Dispenser is between 0.01-999999.99, depending on the quantity ordered. The delivery time for this product is between 20-30 days, ensuring that customers receive their orders on time.

In conclusion, the Virette CD-100 CNG Gas Dispenser is a reliable and efficient CNG fueling equipment that can be used in various application occasions and scenarios. Its high-quality build, range of features, and affordable price make it an excellent choice for organizations looking to refuel their CNG-powered vehicles and equipment.

Customization:

- Brand Name: Virette
- Place of Origin: China
- Delivery Time: 20 30 days
- Humidity Range: ≤95%
- Flow Rate: 15-25L/min

vr more products please visit us on refueling-equipment.com

- Model: CD-100

- Hose Length: 4m

- Temperature Range: -25 To +55

Our experts can customize the CNG Filling Station Dispenser to fit your specific needs. We can work with you to create a Natural Gas Dispensing System that meets your unique requirements. Contact us today to learn more about our product customization services.

Packing and Shipping:

Product Packaging:

The CNG Gas Dispenser will be securely packaged in a sturdy cardboard box to prevent any damage during transport.

The product will be wrapped in bubble wrap to provide additional protection.

The box will also contain a user manual and any necessary accessories. Shipping:

The CNG Gas Dispenser will be shipped via a reputable courier service.

Shipping will be calculated based on the destination and weight of the package.

Customers will receive a tracking number once the package has been shipped.

Delivery times may vary depending on the destination.

Virette Technology Co., Ltd.

+8615651807973

ryan.s@youngtiontech.com (C) refueling-equipment.com

Shizishu Industrial Concentration Zone, GuxiongStreet, Yuhuatai District, Nanjing City, Jiangsu Province, China